



EYE TO EYE (SHACKLE) SPRINGS 45MM X 8MM

Capacity for two springs	Description	Length of spring from eye to tail	Free Camber	Eye to Centre Bolt	Shackle Bolt Diameter	Spring Bush Dimensions	Single Axle Set up dimension "A" (No Load)	Tandem Axle set up dimension "B" & "C" (No Load)	B	C	Nominal Axle Centres Minimum "D"	Part Number for one spring (No hangers included)	Spring surface finish
700 kg	45mm x 8mm x 2 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES2916 ES2G	BLACK GALVANISED
850 kg	45mm x 8mm x 3 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES3916 ES3G	BLACK GALVANISED
1100 kg	45mm x 8mm x 4 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES4916 ES4G	BLACK GALVANISED
1300 kg	45mm x 8mm x 5 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES5916 ES5G	BLACK GALVANISED
1500 kg	45mm x 8mm x 6 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES6916 ES6G	BLACK GALVANISED
1900 kg	45mm x 8mm x 8 leaf	711mm	120mm	355mm	9/16"	9/16" x 45mm	735mm		830mm	825mm	960mm	ES8916 ES8G	BLACK GALVANISED